

SHENKAI

SK-CMS
CAN



SK-CMS


-
- CAN
-
-
-
-
-
-
-

WITS

PDF




380V 480V 440V 220V



50Hz

380V ± 5%



50Hz

SNQ

	220V ± 10%
	35~65Hz
	220V ± 2%
	50 ± 1Hz
	≥ 15min

2MΩ
.

30 90s
C1 nC5
1 × 10-6 1 × 10-6
1 × 10-6 1 1 × 10-6 1
≥ 0.85 1% C1/C2 300:1
≤ 0.5% F.S/h
≤ 1% F.S/h
≤ 2.5% F.S

CO2
CO2 0.1%
CO2 0.1% 100%
1 /7d

± 5

--

/	0-1920 /
---	----------

0~6MPa

0~42MPa

0~68MPa

0~6MPa

0~125

0~3g/cm³

0~50ms/cm 0~300ms/cm

0~100% ()

0~5m

0~9999	0 50m
--------	-------

0 100ppm	T80 30s
----------	---------

--

0~100

1

--

1~3g/cm³

0.05g

0.01g/cm³



220VAC 50Hz

40W



220VAC 50Hz

300W

≤ 1.3KPa

1.3KPa	2
--------	---



380VAC

370W

1400rpm

ExdIIBT4
